

MODEL KONTAKT 40/K GREEN LINE

CZECH UP YOUR BEER COOLING AND DISPENSING SYSTEMS

Dispensing systems from the KONTAKT 40 series are designed for professional cooling, dispensing and serving of perfectly chilled and other beverages at home, on garden parties, company celebrations and smaller commercial events, with ability to dispense up to 2 beverages at once (two-tap variant). Their small size and built-in air system open up new possibilities even in professional environments.

AIR COMPRESSOR

The cooler is fitted with a wholly unique system of a builtin, silent, high-quality air compressor fitted with a noise dampener and a molecule filter for incoming air. The air system is fully automated and set to an operating pressure of 2.8 - 3.2 bar.



BENEFIT AND FUNCTIONAL CHARACTERISTICS OF LINDR CONTACT DISPENSING SYSTEMS:

GREEN LINE – LINDR GREEN LINE technology is environmentally friendly thanks to the use of ecofriendly refrigerant R-290. We have introduced an energy saving system in the production. Thanks to this design, each product achieves **20% higher energy efficiency and 20% lower energy consumption**.

LINDR THERMAL BLOCK – the compressor cooling unit uses the power input for direct transfer to chilling, which guarantees minimum energy usage. Perfectly chilled beer is ready within a few minutes after switching the cooler on.

LINDR COOLING TECHNOLOGY – always more powerful than its electric input power.

STAINLESS CONSTRUCTION – The entire body and the coil of the cooler are made of stainless steel. The materials used meet the strictest hygienic standards and quarantee long service life of the cooler.

PERFORMANCE, QUALITY, SIZE – the best performance/ quality/ size ratio.

VERSATILITY – Can also be used with a bar dispense tower.

- ✓ **GREEN LINE** all models in the KONTAKT 40 series come in full GREEN LINE design.
- ✓ **IMPROVED PERFORMANCE** KONTAKT 40 series dispensing systems boast a continuous output of 40-50 l/h, allowing you to serve 80-100 perfectly chilled drinks an hour.
- ✓ **KEG PRESSURISATION** MODELS KONTAKT 40/K 1x tap and 40/K are equipped with a unique system of a built-in, silent, high-quality air compressor fitted with a noise dampener, a molecule filter for incoming air and automatic operating pressure setting.
- ✓ **PERFECT DRAUGHT BEER** model KONTAKT 40/K PROFI is fitted with a regulator with pressure gauge to set the optimal pressure for dispensing different types of beverages.
- ✓ **COMFORTABLY PORTABLE** ease and safety of handling is maintained thanks to the system's relatively small size and two handles located on top.
- ✓ **EQUIPMENT** thermostat allowing smooth and precise regulation of beverage temperature, dispensing tap(s), drip tray and speedfit fittings for easy connection.

TECHNICAL PARAMETERS







AVAILABLE CUSTOM MODIFICATION OPTIONS	YES
CHOICE OF TAPS	✓
BEER/ AIR STAINLESS STEEL SCREWING - G 5/8"	\checkmark
POWER CABLE PLUG	✓

Selected models are also available in 115 V/60 Hz or 220 V/60 Hz voltage. Other custom modifications are also available (contact us).

PRODUCT MODEL	KONTAKT 40/K GL
COOLING POWER OF THE COMPRESSOR (HP)	1/5
COOLING POWER OF THE COMPRESSOR (W)	510
MAXIMUM COOLING CAPACITY TO 0°C / TK 45°C (L/HOUR)	50
CONTINOUS COOLING PERFORMANCE (L/HOUR)	40
THERMAL GRADIENT AT (°C)	10
AIR COMPRESSOR (BAR)	YES, AUTOMATIC 2,8-3,2
NUMBER OF TAPS (PCS)	2
NUMBER/ LENGHT OF COOLING COILS (M)	2/ 14,0
POWER (W)	391
AMPERAGE (A)	1,70
NET WEIGHT (KG)	29,0
TYPE OF REFRIGERANT	R290
VOLTAGE	220-240V 50HZ~1
CONECTION BEER/ AIR - SPEEDFIT FITTINGS	3/8, 5/16





